

CTS 22 - CTS 40 - CTT 40

© 2008 Nilfisk-CFM S.p.A. - A20 GB 08 I Data, technical characteristics, colors and illustrations can be subject to change without prior notice



Nilfisk-CFM S.p.A.
Via Porrettana 1991
41059 Zocca (Modena) Italy
Tel. +39 059 9730000
Fax +39 059 9730099

www.nilfisk-cfm.it
info@nilfisk-cfm.it

- please call me by phone
- I need a visit of a vacuums specialist
- please send me free documentation

CTS 22- CTS 40- CTT 40

Company: _____ Mrs./Mr.: _____
Function: _____ Address: _____
ZIP: _____ City: _____ Prov./State: _____
Tel.: _____ Fax: _____ Mobile: _____
E-mail: _____

Compact, versatile and silent

The new industrial vacuums CTT and CTS by Nilfisk-CFM

L, M, H and ATEX versions available



CTS 22 - 40



CTT 40



Packaging



Pharmaceutical



Chemicals



Electronics



Food



Metalworking engineering



Ceramics



Rubber e plastic



Textile



Marble/Stone carving

Nilfisk-CFM introduces a new range of threephase industrial vacuums equipped with lateral channel blower or turbine. The compact size offers many opportunities: possibility to operate even in the most inaccessible places, lightness, easy movement. It is possible choosing between models with great depression and reduced airflow (models CTS 22 (2,2 kW) and CTS 40 (4 kW)) or models equipped with a turbine blower releasing a great airflow and less depression (CTT 40). The full range is available in L, M, H and ATEX versions. Compact and powerful industrial vacuums: the true solution for those who want everything!



Container transport and discharge system with lift truck



Compact and elegant design



Turbine or lateral channel vacuum unit

Master description	CTS22 Standard	CTS40L	CTT40L
Part no.	4030600036	4030600032	4030600034
IP PROTECTION CLASS	55	55	55
INSULATION CLASS	F	F	F
RATED POWER (kW)	2,2	4	4
VOLTAGE (V)	230/400	230/400	230/400
SOUND PRESSURE LEVEL AT 1.5 M (dB(A) ISO 374)	68	70	73
AIRFLOW WITHOUT HOSE (L/s)	88	117	148
VACUUM MAX (mBar)	300	300	180
CONTAINER CAPACITY (l)	50	50	50
LENGTH X WIDTH X HEIGHT (cm)	105x60x125	105x60x125	105x60x125
WEIGHT (kg)	99	114	119

Advantages and benefits

CTS and CTT models are the ideal tool for the needs of many productive contexts thank to their features:

Versatile: the possibility to choose the type of motor makes these industrial vacuums suitable for any situation;

Modular: the wide range of filters allows an excellent filtration of any kind of material (very fine dust, hazardous material etc...);

Practical: small size is its strength: ease of movement, manoeuvrability, possibility to reach any place, even the most inaccessible;

Powerful: the threephase motor grants high performances, these models can operate continuously without any problem;

Safe: low noise levels, high filtration efficiency, L, M, H, ATEX versions available;

Ergonomic: rounded shape and handles are the main design feature of this range, allowing operators to easily move the vacuum which can be seized by all sides. These shapes prevent the deposit of materials on the vacuum surface, keeping it always clean. The new release system allows to easily remove and empty the bin.



Collection of pasta, flour and sugar



Collection from marble carving



Collection of shavings from a machine tool